

BLOCK-OUT ALL
FIRST FLOOR SWITCHES
FOR 1x6 TRIM

BLOCK-OUT ALL
SECOND FLOOR SWITCHES
FOR 1x4 TRIM

ELECTRICAL LEGEND

○	110 VOLT RECEPTACLE
○	WATERPROOF RECEPTACLE
○	IN FLOOR
○	110 VOLT W/ GROUND FAULT INTERRUPTER
○	220V 220 VOLT RECEPTACLE
—	CABLE
○	GAS OUTLET
○	TELEPHONE OUTLET
○	LAMB SWITCH
○	FLOODS ON PHOTO CELL
○	UNDER CAB. STRIP LIGHT
○	SINGLE POLE SWITCH
○	THREE WAY SWITCH
○	FOUR WAY SWITCH
○	DIMMER SWITCH
○	PENDANT LIGHT
○	HANGING LIGHT
○	RECESSED CAN LIGHT
○	WATERPROOF RECESSED CAN LIGHT
○	SMOKE DETECTOR
○	DIRECTIONAL RECESSED CAN LIGHT
○	CEILING MOUNT FIXTURE
○	EXHAUST FAN
○	EXHAUST FAN W/ LIGHT KIT
○	WALL MOUNTED LIGHT
○	WALL MOUNTED PHOTO CELL LIGHT
○	HOSE BIB
○	FLUORESCENT FLUORESCENT FIXTURE
○	2x2 FLUORESCENT FIXTURE
○	CENSOR
○	150W HALOGEN
○	FAN
○	42" OUTSIDE FAN

ELECTRICAL NOTES

- 1) GAS WATER HEATER
- 2) HARD WIRE HOUSE FOR SECURITY SYSTEM. SECURITY SYSTEM TO BE SELECTED BY OWNER
- 3) SECURITY SYSTEM WILL BE INSTALLED PRIOR TO APPLICATION OF DRY WALL AND ACCORDING TO MANUFACTURERS SPECS. AS NEGOTIATED BY OWNER UNDER SEPARATE CONTRACT.
- 4) SMOKE DETECTORS TO BE HARDWIRED INTER-CONNECTED WITH BATTERY BACK-UP AS REQUIRED BY THE IRC R317.1.
- 5) MIN. 2 LIGHTS IN EACH ATTIC AREA.

